

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Version 11.0

Revision Date 25.03.2024

Print Date 27.03.2024

GENERIC EU MSDS - NO COUNTRY SPECIFIC DATA - NO OEL DATA

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : Xylenes (isomeric mixture) for analysis
EMPARTA® ACS

Product Number : 1.08633
Catalogue No. : 108633
Brand : Millipore

UFI : E821-X6E5-R99U-USX4

REACH No. : This product is a mixture. REACH Registration Number see section 3.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Reagent for analysis, Solvent
Uses advised against : This product is not intended for consumer use.

1.3 Details of the supplier of the safety data sheet

Company : Merck KGaA
Frankfurter Str. 250
D-64271 DARMSTADT

Telephone : +49 (0)6151 72-0
Fax : +49 6151 727780
E-mail address : TechnicalService@merckgroup.com

1.4 Emergency telephone

Emergency Phone # : +(44)-870-8200418 (CHEMTREC (GB))
+(353)-19014670 (CHEMTREC Ireland)
001-803-017-9114 (CHEMTREC India)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Flammable liquids, (Category 3) H226: Flammable liquid and vapor.

Acute toxicity, (Category 4) H332: Harmful if inhaled.



Acute toxicity, (Category 4)	H312: Harmful in contact with skin.
Skin irritation, (Category 2)	H315: Causes skin irritation.
Eye irritation, (Category 2)	H319: Causes serious eye irritation.
Specific target organ toxicity - single exposure, (Category 3), Respiratory system	H335: May cause respiratory irritation.
Specific target organ toxicity - repeated exposure, (Category 2), hearing organs	H373: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard, (Category 1)	H304: May be fatal if swallowed and enters airways.
Long-term (chronic) aquatic hazard, (Category 3)	H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according Regulation (EC) No 1272/2008

Pictogram



Signal Word

Danger

Hazard Statements

H226	Flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H312 + H332	Harmful in contact with skin or if inhaled.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H373	May cause damage to organs (hearing organs) through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Precautionary Statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P273	Avoid release to the environment.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P331	Do NOT induce vomiting.

Supplemental Hazard Statements

none



Reduced Labeling (<= 125 ml)

Pictogram



Signal Word

Danger

Hazard Statements

H304

May be fatal if swallowed and enters airways.

H412

Harmful to aquatic life with long lasting effects.

Precautionary Statements

P301 + P310

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331

Do NOT induce vomiting.

Supplemental Hazard Statements

none

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information:

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information:

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Component		Classification	Concentration
m-xylene			
CAS-No.	108-38-3	Flam. Liq. 3; Acute Tox. 4; Skin Irrit. 2; Eye Irrit. 2; STOT SE 3; Asp. Tox. 1; Aquatic Chronic 3; H226, H332, H312, H315, H319, H335, H304, H412	>= 30 - < 50 %
EC-No.	203-576-3		
Index-No.	601-022-00-9		
Registration number	01-2119484621-37-XXXX		
p-xylene			
CAS-No.	106-42-3	Flam. Liq. 3; Acute Tox. 4; Skin Irrit. 2; Eye Irrit. 2; STOT SE 3; Asp. Tox. 1; Aquatic Chronic 3; H226, H332, H312, H315, H319, H335, H304, H412	>= 20 - < 25 %
EC-No.	203-396-5		
Index-No.	601-022-00-9		
Registration number	01-2119484661-33-XXXX		



ethylbenzene			
CAS-No.	100-41-4	Flam. Liq. 2; Acute Tox. 4;	>= 10 - < 20 %
EC-No.	202-849-4	STOT RE 2; Asp. Tox. 1;	
Index-No.	601-023-00-4	Aquatic Chronic 3; H225,	
Registration number	01-2119489370-35-XXXX	H332, H373, H304, H412	
o-xylene			
CAS-No.	95-47-6	Flam. Liq. 3; Acute Tox. 4;	>= 10 - < 20 %
EC-No.	202-422-2	Skin Irrit. 2; Eye Irrit. 2;	
Index-No.	601-022-00-9	STOT SE 3; Asp. Tox. 1;	
Registration number	01-2119485822-30-XXXX	Aquatic Chronic 3; H226, H332, H312, H315, H319, H335, H304, H412	
Toluene			
CAS-No.	108-88-3	Flam. Liq. 2; Skin Irrit. 2;	>= 0,25 - < 1 %
EC-No.	203-625-9	Repr. 2; STOT SE 3; STOT	
Index-No.	601-021-00-3	RE 2; Asp. Tox. 1; Aquatic	
Registration number	01-2119471310-51-XXXX	Chronic 3; H225, H315, H361d, H336, H373, H304, H412 Concentration limits: 20 %: STOT SE 3, H336;	

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Immediately call in physician. If breathing stops: immediately apply artificial respiration, if necessary also oxygen.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Consult a physician.

In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

If swallowed

After swallowing: caution if victim vomits. Risk of aspiration! Keep airways free. Pulmonary failure possible after aspiration of vomit. Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11



4.3 Indication of any immediate medical attention and special treatment needed No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂) Dry powder Foam

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Combustible.

Vapors are heavier than air and may spread along floors.

Forms explosive mixtures with air at elevated temperatures.

Development of hazardous combustion gases or vapours possible in the event of fire.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Advice on protection against fire and explosion



Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

Recommended storage temperature see product label.

Storage class

Storage class (TRGS 510): 3: Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

8.2 Exposure controls

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact

Material: Viton®

Minimum layer thickness: 0,70 mm

Break through time: 480 min

Material tested: Vitoject® (KCL 890 / Aldrich Z677698, Size M)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Splash contact



Material: Nitrile rubber
Minimum layer thickness: 0,40 mm
Break through time: 30 min
Material tested: Camatril® (KCL 730 / Aldrich Z677442, Size M)

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

Recommended Filter type: Filter A (acc. to DIN 3181) for vapours of organic compounds

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Physical state	liquid
b) Color	colorless
c) Odor	sweet
d) Melting point/freezing point	Melting point/range: -47 °C
e) Initial boiling point and boiling range	137 - 143 °C
f) Flammability (solid, gas)	No data available
g) Upper/lower flammability or explosive limits	Upper explosion limit: 6,6 %(V) Lower explosion limit: 1,1 %(V)
h) Flash point	26 °C - c.c.
i) Autoignition temperature	466 °C
j) Decomposition temperature	No data available
k) pH	substance/mixture is non-polar/aprotic
l) Viscosity	Viscosity, kinematic: No data available Viscosity, dynamic: No data available
m) Water solubility	No data available
n) Partition coefficient: n-octanol/water	No data available



- | | |
|-----------------------------|------------------------------|
| o) Vapor pressure | No data available |
| p) Density | No data available |
| Relative density | No data available |
| q) Relative vapor density | No data available |
| r) Particle characteristics | No data available |
| | |
| s) Explosive properties | Not classified as explosive. |
| t) Oxidizing properties | none |

9.2 Other safety information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Vapor/air-mixtures are explosive at intense warming.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

10.3 Possibility of hazardous reactions

Violent reactions possible with:

Strong oxidizing agents

conc. sulfuric acid

sulfur

Risk of explosion with:

Nitric acid

uranium hexafluoride

10.4 Conditions to avoid

Heating.

10.5 Incompatible materials

Rubber, various plastics, Light metals

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Mixture

Acute toxicity

Symptoms: Irritations of mucous membranes in the mouth, pharynx, oesophagus and gastrointestinal tract.



Acute toxicity estimate Inhalation - 4 h - 11,7 mg/l - vapor(Calculation method)

Symptoms: Possible symptoms:, mucosal irritations, Cough, Shortness of breath, Possible damages:, damage of respiratory tract

Acute toxicity estimate Dermal - 1.334 mg/kg
(Calculation method)

Skin corrosion/irritation

Remarks: Mixture causes skin irritation.

Serious eye damage/eye irritation

Remarks: Mixture causes serious eye irritation.

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

Mixture may cause respiratory irritation.

Specific target organ toxicity - repeated exposure

Mixture may cause damage to organs through prolonged or repeated exposure.
- hearing organs

Aspiration hazard

Aspiration hazard, Aspiration may cause pulmonary edema and pneumonitis.

11.2 Additional Information

Endocrine disrupting properties

Product:

Assessment

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Other dangerous properties can not be excluded.

Handle in accordance with good industrial hygiene and safety practice.



Components

m-xylene

Acute toxicity

LD50 Oral - Rat - male - 3.523 mg/kg

(EC Directive 92/69/EEC B.1 Acute Toxicity (Oral))

LC50 Inhalation - Rat - female - 4 h - 29,091 mg/l - vapor

Remarks: (Regulation (EC) No 1272/2008, Annex VI)
(ECHA)

Symptoms: Inhalation may lead to the formation of oedemas in the respiratory tract.

LD50 Dermal - Rabbit - male - 12.126 mg/kg

Remarks: (ECHA)

Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Skin corrosion/irritation

Skin - Rabbit

Result: Moderate skin irritation - 4 h

(Regulation (EC) No. 440/2008, Annex, B.4)

Remarks: After long-term exposure to the chemical:

Dermatitis

Drying-out effect resulting in rough and chapped skin.

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Moderate eye irritation

Remarks: (ECHA)

Respiratory or skin sensitization

Local lymph node assay (LLNA) - Mouse

Result: negative

(OECD Test Guideline 429)

Germ cell mutagenicity

Test Type: sister chromatid exchange assay

Test system: Chinese hamster ovary cells

Result: negative

Test Type: Ames test

Test system: Salmonella typhimurium

Result: negative

Remarks: (National Toxicology Program)

Test Type: Mutagenicity (mammal cell test): chromosome aberration.

Test system: Chinese hamster ovary cells

Result: negative

Method: OECD Test Guideline 478

Species: Mouse - male and female

Result: negative

Method: OECD Test Guideline 474

Species: Mouse - male - Red blood cells (erythrocytes)

Result: negative

Remarks: (IUCLID)



Carcinogenicity

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

Reproductive toxicity

Overexposure may cause reproductive disorder(s) based on tests with laboratory animals.

Specific target organ toxicity - single exposure

Inhalation - May cause respiratory irritation. - Respiratory Tract

Acute inhalation toxicity - Inhalation may lead to the formation of oedemas in the respiratory tract.

Specific target organ toxicity - repeated exposure**Aspiration hazard**

May be fatal if swallowed and enters airways.

p-xylene**Acute toxicity**

LD50 Oral - Rat - male - 3.523 mg/kg

(EC Directive 92/69/EEC B.1 Acute Toxicity (Oral))

Acute toxicity estimate Inhalation - 4 h - 10,1 mg/l - vapor

(Expert judgment)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Acute toxicity estimate Dermal - 1.000,1 mg/kg

(Expert judgment)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Skin corrosion/irritation

Skin - Rabbit

Result: Moderate skin irritation - 4 h

(Regulation (EC) No. 440/2008, Annex, B.4)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Remarks: Drying-out effect resulting in rough and chapped skin.

Dermatitis

Serious eye damage/eye irritation

Remarks: Causes serious eye irritation.

(ECHA)

Respiratory or skin sensitization

Local lymph node assay (LLNA) - Mouse

Result: negative

(OECD Test Guideline 429)

Germ cell mutagenicity

Test Type: Ames test

Test system: Salmonella typhimurium

Result: negative

Remarks: (National Toxicology Program)



Test Type: sister chromatid exchange assay
Test system: Chinese hamster ovary cells
Result: negative
Test Type: Mutagenicity (mammal cell test): chromosome aberration.
Test system: Chinese hamster ovary cells
Result: negative
Method: OECD Test Guideline 474
Species: Mouse - male - Red blood cells (erythrocytes)
Result: negative
Remarks: (IUCLID)
Method: OECD Test Guideline 478
Species: Mouse - male and female
Result: negative

Carcinogenicity

No data available

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

Inhalation - May cause respiratory irritation. - Respiratory Tract

Specific target organ toxicity - repeated exposure

Aspiration hazard

May be fatal if swallowed and enters airways.

ethylbenzene

Acute toxicity

LD50 Oral - Rat - male and female - 3.500 mg/kg

Remarks: (ECHA)

LC50 Inhalation - Rat - male - 4 h - 17,8 mg/l - vapor

Remarks: (ECHA)

Acute toxicity estimate Inhalation - 17,8 mg/l - vapor
(ATE value derived from LD50/LC50 value)

LD50 Dermal - Rabbit - 15.433 mg/kg

Remarks: (RTECS)

Skin corrosion/irritation

Skin - Rabbit

Result: Moderate skin irritation - 24 h

Remarks: (ECHA)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Mild eye irritation

Remarks: (ECHA)

Respiratory or skin sensitization

No data available



Germ cell mutagenicity

Test Type: Chromosome aberration test in vitro

Test system: Chinese hamster ovary cells

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Test system: mouse lymphoma cells

Result: negative

Method: OECD Test Guideline 474

Species: Mouse - male - Bone marrow

Result: negative

Method: OECD Test Guideline 486

Species: Mouse - male and female

Result: negative

Carcinogenicity

No data available

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

- hearing organs

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Aspiration hazard

Aspiration may cause pulmonary edema and pneumonitis.

o-xylene

Acute toxicity

LD50 Oral - Rat - male - 3.523 mg/kg

(EC Directive 92/69/EEC B.1 Acute Toxicity (Oral))

LC50 Inhalation - Rat - male and female - 4 h - 27,12 mg/l - vapor

(US-EPA)

Symptoms: Inhalation may lead to the formation of oedemas in the respiratory tract.

Symptoms: mucosal irritations, Cough, Shortness of breath, Possible damages:, damage of respiratory tract

Dermal: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Skin corrosion/irritation

Skin - Rabbit

Result: Moderate skin irritation - 4 h

(Regulation (EC) No. 440/2008, Annex, B.4)

Remarks: Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

Serious eye damage/eye irritation

No data available



Respiratory or skin sensitization

Local lymph node assay (LLNA) - Mouse

Result: negative

(OECD Test Guideline 429)

Germ cell mutagenicity

Test Type: Ames test

Test system: Salmonella typhimurium

Result: negative

Test Type: Mutagenicity (mammal cell test): chromosome aberration.

Test system: Chinese hamster ovary cells

Result: negative

Test Type: sister chromatid exchange assay

Test system: Chinese hamster ovary cells

Result: negative

Method: OECD Test Guideline 474

Species: Mouse - male - Red blood cells (erythrocytes)

Result: negative

Remarks: (IUCLID)

Method: OECD Test Guideline 478

Species: Mouse - male and female

Result: negative

Carcinogenicity

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

Inhalation - May cause respiratory irritation. - Respiratory system

Acute inhalation toxicity - Inhalation may lead to the formation of oedemas in the respiratory tract.

Acute inhalation toxicity - mucosal irritations, Cough, Shortness of breath, Possible damages:, damage of respiratory tract

Specific target organ toxicity - repeated exposure

Aspiration hazard

May be fatal if swallowed and enters airways. Aspiration hazard, Aspiration may cause pulmonary edema and pneumonitis.

Toluene

Acute toxicity

LD50 Oral - Rat - male - 5.580 mg/kg

(Directive 67/548/EEC, Annex V, B.1.)

LC50 Inhalation - Rat - male - 4 h - 25,7 mg/l - vapor

(OECD Test Guideline 403)

LD50 Dermal - Rabbit - male - > 5.000 mg/kg

Remarks: (ECHA)



Skin corrosion/irritation

Skin - Rabbit

Result: irritating - 4 h

(Regulation (EC) No. 440/2008, Annex, B.4)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: No eye irritation

(OECD Test Guideline 405)

Respiratory or skin sensitization

Maximization Test - Guinea pig

Result: negative

(Regulation (EC) No. 440/2008, Annex, B.6)

Germ cell mutagenicity

Test Type: In vitro mammalian cell gene mutation test

Test system: Mouse lymphoma test

Result: negative

Test Type: Ames test

Test system: *S. typhimurium*

Result: negative

Species: Rat - Bone marrow

Result: negative

Remarks: (ECHA)

Carcinogenicity

No data available

Reproductive toxicity

Suspected of damaging the unborn child.

Specific target organ toxicity - single exposure

Inhalation - May cause drowsiness or dizziness. - Central nervous system

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Specific target organ toxicity - repeated exposure

Inhalation - May cause damage to organs through prolonged or repeated exposure.

- Central nervous system

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Aspiration hazard

Aspiration may cause pulmonary edema and pneumonitis.

SECTION 12: Ecological information**12.1 Toxicity****Mixture**

No data available

12.2 Persistence and degradability

No data available



12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

No data available

Components

m-xylene

Toxicity to fish	static test LC50 - Oncorhynchus mykiss (rainbow trout) - 2,60 mg/l - 96 h (OECD Test Guideline 203)
Toxicity to algae	static test EC50 - Pseudokirchneriella subcapitata - 4,36 mg/l - 73 h (OECD Test Guideline 201)
Toxicity to bacteria	Remarks: (ECHA)
Toxicity to fish(Chronic toxicity)	flow-through test NOEC - Danio rerio (zebra fish) - 0,71 mg/l - 35 d (OECD Test Guideline 210)
Toxicity to daphnia and other aquatic invertebrates(Chronic toxicity)	NOEC - Daphnia magna (Water flea) - 1,57 mg/l - 21 d (OECD Test Guideline 211)

p-xylene

Toxicity to fish	static test LC50 - Oncorhynchus mykiss (rainbow trout) - 2,60 mg/l - 96 h (OECD Test Guideline 203)
Toxicity to daphnia and other aquatic invertebrates	EC50 - Daphnia magna (Water flea) - 35,50 - 63,10 mg/l - 48 h Remarks: (ECOTOX Database)
Toxicity to algae	static test ErC50 - Pseudokirchneriella subcapitata - 4,36 mg/l



	- 73 h (OECD Test Guideline 201)
Toxicity to bacteria	static test NOEC - activated sludge - 16,2 mg/l - 28 h Remarks: (ECHA)
Toxicity to fish(Chronic toxicity)	flow-through test NOEC - Danio rerio (zebra fish) - 0,71 mg/l - 35 d (OECD Test Guideline 210)
Toxicity to daphnia and other aquatic invertebrates(Chronic toxicity)	static test EC50 - Daphnia magna (Water flea) - 2,9 mg/l - 21 d (OECD Test Guideline 211)
	static test NOEC - Daphnia magna (Water flea) - 1,57 mg/l - 21 d (OECD Test Guideline 211)

ethylbenzene

Toxicity to fish	semi-static test LC50 - Oncorhynchus mykiss (rainbow trout) - 4,2 mg/l - 96 h (OECD Test Guideline 203)
Toxicity to daphnia and other aquatic invertebrates	static test EC50 - Daphnia magna (Water flea) - 1,8 - 2,4 mg/l - 48 h (US-EPA)
Toxicity to algae	static test EC50 - Pseudokirchneriella subcapitata (green algae) - 3,6 mg/l - 96 h (US-EPA)
Toxicity to bacteria	EC50 - Photobacterium phosphoreum - 9,68 mg/l - 30 min Remarks: (IUCLID)

o-xylene

Toxicity to fish	static test LC50 - Oncorhynchus mykiss (rainbow trout) - 2,60 mg/l - 96 h (OECD Test Guideline 203)
Toxicity to algae	static test EC50 - Pseudokirchneriella subcapitata - 4,36 mg/l - 73 h (OECD Test Guideline 201)
Toxicity to bacteria	Remarks: (ECHA)
Toxicity to fish(Chronic toxicity)	flow-through test NOEC - Danio rerio (zebra fish) - 0,71 mg/l - 35 d (OECD Test Guideline 210)
Toxicity to daphnia and other aquatic invertebrates(Chronic toxicity)	NOEC - Daphnia magna (Water flea) - 1,57 mg/l - 21 d (OECD Test Guideline 211)



toxicity)

EC50 - Daphnia magna (Water flea) - 2,9 mg/l - 21 d
(OECD Test Guideline 211)

Toluene

Toxicity to fish flow-through test LC50 - Oncorhynchus kisutch (coho salmon) -
5,5 mg/l - 96 h
Remarks: (ECHA)

Toxicity to daphnia EC50 - Ceriodaphnia dubia (water flea) - 3,78 mg/l - 48 h
and other aquatic (US-EPA)
invertebrates

Toxicity to bacteria static test EC50 - Bacteria - 84 mg/l - 24 h
Remarks: (ECHA)

Toxicity to flow-through test NOEC - Oncorhynchus kisutch (coho salmon)
fish(Chronic toxicity) - 1,39 mg/l - 40 d
Remarks: (ECHA)

Toxicity to daphnia NOEC - Ceriodaphnia dubia (water flea) - 0,74 mg/l - 7 d
and other aquatic (US-EPA)
invertebrates(Chronic
toxicity)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

No data available

SECTION 14: Transport information

14.1 UN number

ADR/RID: 1307

IMDG: 1307

IATA: 1307

14.2 UN proper shipping name

ADR/RID: XYLENES, SOLUTION

IMDG: XYLENES, SOLUTION

IATA: Xylenes, SOLUTION

14.3 Transport hazard class(es)

ADR/RID: 3

IMDG: 3

IATA: 3



14.4 Packaging group

ADR/RID: III

IMDG: III

IATA: III

14.5 Environmental hazards

ADR/RID: no

IMDG Marine pollutant: no

IATA: no

14.6 Special precautions for user

Tunnel restriction code : (D/E)

Further information : No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.

Authorisations and/or restrictions on use

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Toluene
benzene

National legislation

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS

Other regulations

Observe work restrictions regarding maternity protection in accordance to Dir 92/85/EEC or stricter national regulations where applicable.

Take note of Dir 94/33/EC on the protection of young people at work.

15.2 Chemical Safety Assessment

For this product a chemical safety assessment was not carried out

SECTION 16: Other information

Full text of H-Statements

H225	Highly flammable liquid and vapor.
H226	Flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.



- H373 May cause damage to organs through prolonged or repeated exposure if inhaled.
- H412 Harmful to aquatic life with long lasting effects.

Relevant changes since previous version

2. Hazards identification

Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Classification of the mixture

Flam. Liq.3	H226
Acute Tox.4	H332
Acute Tox.4	H312
Skin Irrit.2	H315
Eye Irrit.2	H319
STOT SE3	H335

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method



STOT RE2	H373	Calculation method
Asp. Tox.1	H304	Calculation method
Aquatic Chronic3	H412	Calculation method

Further information

The information is believed to be correct but is not exhaustive and will be used solely as a guideline, which is based on current knowledge of the chemical substance or mixture and is applicable to appropriate safety precautions for the product. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

